

IMPACT TH-1100

Portable Dynamic Hardness Tester






IMPACT TH-1100
PORTABLE LEEB HARDNESS TESTER

FEATURES

The IMPACT TH-1100 is a small, integrated digital hardness tester which operates according to the dynamic rebound method (standardized according to ASTM A956). The compact design allows easy on-site hardness testing on solid, components that are difficult to transport, or to be used on positions difficult to access by other hardness testers. Quick and reproducible measurements can be made independent of impact direction.

- Leeb principle, portable rebound hardness tester
- Hardness values in Rockwell HRB, HRC, Vickers HV, Brinell HB, Shore HS, Leeb HLD
- Test results appear directly on the display
- Impact Device D integrated: no cables
- Tests at any angle, even upside down
- Bright LCD display
- Battery capacity on display
- Rechargeable Li-on battery
- Simple handling and low test expenditure



STANDARD DELIVERY

- Instrument with integrated impact device, type D
- Hardness test block with HLD value
- Coupling paste
- Support ring small
- Charger
- Cleaning brush
- INNOVATEST® certificate
- Manual
- Carrying case

TECHNICAL SPECIFICATIONS

Standard impact device	D integrated
Hardness scales	HRC, HRB, HV, HB, HS & HLD
Measuring range / materials	See table
Accuracy	±6HLD
Output	No
Min. surface roughness of workpiece	1.6µm (Ra)
Max. workpiece hardness	960HLD
Min. radius of workpiece	Rmin= 50mm (convex/concave) (with support ring Rmin= 10mm)
Min. workpiece weight	2.5kg on stable support 0.05-2kg with compact coupling
Min. workpiece thickness coupled	5mm
Min. thickness of hardened layers	0.8mm
Charging time	3 hours
Continuous working time	> 8 hours
Power	Rechargeable Li battery
Operating temperature	0°C to 40°C
Overall dimensions	145mm x 35mm x 30mm
Weight	110gr

ORDER DETAILS

TH-1100 Portable dynamic hardness tester

MEASURING RANGE

Material	HLD	HRB	HRC	HB	HV	HS
Steel & cast steel	300-900	38.4-99.8	20-68.4	81-654	81.1-955	32.5-99.5
Cold work tool steel	300-840		20.4-67.1		80-898	
Stainless steel	300-800	46.5-101.7	19.6-62.4	85-655	85-802	
Gray cast iron	360-650			93-334		
Nodular cast iron	400-660			131-387		
Cast aluminum	200-570	23.8-34.6		26.8-164		
Brass	200-550	13.5-95.3		40-173		
Bronze	300-700			60-290		
Copper	200-690			45-315		
Wrought steel				143-650		

OPTIONAL ACCESSORIES

- UKAS Reference hardness blocks
- Type Z10-15, for testing cylindrical outside surface R10~R15
- Type Z14.5-30, for testing cylindrical outside surface R14.5~R30
- Type Z25-50, for testing cylindrical outside surface R25~R50
- Type HZ11-13, for testing cylindrical inside surface R11~R13
- Type HZ12.5-17, for testing cylindrical inside surface R12.5~R17
- Type HZ16.5-30, for testing cylindrical inside surface R16.5~R30
- Type K10-15, for testing spherical outside surface SR10~SR15
- Type K14.5-30, for testing spherical outside surface SR14.5~SR30
- Type HK11-13, for testing spherical inside surface SR11~SR13
- Type HK12.5-17, for testing spherical inside surface SR12.5~SR17
- Type HK16.5-30, for testing spherical inside surface SR16.5~SR30
- Type UN, for testing cylindrical outside surface, radius adjustable R10~∞

Represented by:

CORPORATE HEAD OFFICE

MANUFACTURING, DISTRIBUTION & SERVICE

INNOVATEST Europe BV

Borgharenweg 140
6222 AA Maastricht (The Netherlands)
Phone: +31 43 3520060
Fax: +31 43 3631168
Email: info@innovatest-europe.com

INNOVATEST Benelux BVBA

SALES & SERVICE

Phone: +32 12 779002
Fax: +32 12 779003
E-mail: info@innovatest-benelux.com

INNOVATEST Shanghai Co., Ltd.

DISTRIBUTION, SALES & SERVICE

101, Bld. 7, No. 59 Shennan Road,
Minhang District, Shanghai, P.R. China
Zip code: 201108
Phone: +86 21 34635955
Fax: +86 21 34635269
E-mail: info@innovatest-shanghai.com

Changes in products and/or product specifications can emerge due to new technologies and continuous development. We reserve the right to change or modify specifications of products without prior notice. We recommend you to contact our sales office for up-to-date information.

© All rights reserved

www.innovatest-europe.com